

DS-T227



Key Features

- 2 Megapixel high-performance CMOS
- Analog HD output, up to 1080P resolution
- 2.8 – 12mm vari-focal lens
- True Day/Night, Smart IR
- Up to 30m IR distance
- OSD menu
- 24V AC/ 12V DC (-A)
- Up the Coax(HIKVISION-C protocol)

Specifications

| Camera | |
|----------------------|---|
| Image Sensor | 2MP CMOS Image Sensor |
| Signal System | PAL/NTSC |
| Effective Pixels | 1984(H)*1105(V) |
| Min. illumination | 0.01 Lux @ (F1.2,AGC ON),0 Lux with IR; 0.014 Lux @ (F1.4,AGC ON),0 Lux with IR |
| Shutter Time | 1/25(1/30)s to 1/50,000s |
| Lens | 2.8 - 12 mm @ F1.4 |
| | Angle of view: 105.2° - 32.8° |
| Lens Mount | φ14 |
| Day & Night | ICR |
| Angle Adjustment | Pan: 0 - 355°, Tilt: 0 - 75°, Rotation: 0 - 355° |
| Synchronization | Internal synchronization |
| Video Frame Rate | 1080p@25fps/1080p@30fps |
| HD Video Output | 1 Analog HD output |
| S/N Ratio | >62dB |
| Menu | |
| AGC | High/Medium/Low/Off |
| D/N Mode | Smart IR/Color/BW |
| White Balance | Auto/Manual |
| BLC | Support |
| Language | English |
| Functions | Digital noise reduction, Mirror |
| General | |
| Operating Conditions | -20 °C – 45 °C (-4 °F – 113 °F), Humidity 90% or less (non-condensing) |
| Power Supply | 12 VDC ± 15%, -A: 12 VDC ± 15%, 24 VAC ± 15% |
| Power Consumption | Max. 3W, -A: Max. 4W |
| IR Range | Up to 30m |
| Communication | v Up the coax, Protocol: HIKVISION-C(TVI output) |
| Dimensions | Φ 136 × 101.94 mm (Φ 5.35" × 4.01") |
| Weight | 600 g |

Dimensions

